DK-75432 8MP 32CH DVR (IPC Hybrid)

NOVATEK

Specification:

Model		DK-75432
System	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
Video	Format	IP-CAM: ONVIF Profile S / T ; Analog: NTSC/EIA or PAL/CCIR or AHD/TVI/CVI
	Input	IP-CAM: up to 32-CH 1080p/720p, IP-CAM supports up to 8MP Analog: up to 32-CH AHD/TVI/CVI 8MP, BNC, 1Vp-p /75ohm, Total Max: 32-CH Analog or IP-CAM
	Output	HDMI with resolution up to 3840x2160; VGA, with resolution up to 1920x1080; CVBS
Audio	Input / Output	8 x RCA input + 32-CH Coaxial audio Input ; 1 x RCA output / 1x HDMI output (Optional : 8 x RCA input + 2 x RCA output cable for Max. 16CH Audio Input)
Record	Compression	Audio: ADPCM
	Max frame rate	IP-CAM: 8MP/5MP/1080p/720p, Up to 80Mbps incoming bandwidth for IPCAM Analog: 80fps@8MP, 160fps@8MP-lite, 192fps@5MP, 384fps@5MP-lite, 480fps@4MP-lite, 640fps@3MP-lite, 480fps@1080p, 960fps@1080p-lite/720p/960H
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Display	Split windows	1/4/7/9/16/25/36
	Frame rate	Up to 30/25 FPS per display window
	Digital Zoom	X2, X4, X8, X16
Playback	Max frame rate	80fps@8MP, 160fps@8MP-lite, 192fps@5MP, 384fps@5MP-lite, 480fps@4MP-lite, 640fps@3MP-lite, 480fps@1080p, 960fps@1080p-lite/720p/960H
	Search	Smart search, Date/time search, POS search, Camera, Alarm, Motion & Video loss
	Operation	Play, Fast Forward, Backward, Pause, Stop, Snapshot, etc.
Storage	HDD Capacity	5 x 3.5” SATA HDD + 1 eSATA HDDs
	Backup	USB 2.0 x 2 ; USB 3.0 x 1 ; Self playback for backup files
Alarm	Panic	1 contact (Low Active)
	Input	16 contact (Low Active)
	Output	2 (Normally Open or Normally Closed relay outputs)
	Support	Push alarm & Line notification for portable device; Alarm recording to Google Cloud Drive
Network	Ethernet	1 x RJ-45 10M/100M/1000M bps Ethernet connector
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP, NTP, RTSP, UPnP, P2P
	Remote Users	Up to 8 users simultaneously
	Remote	Support Windows 11/10/8/7, N-streaming live view, I.E/Firefox/Chrome DVR, App for Mac/iPhone/iPad/Android phone and Tablet PC
Control / POS / GPS	RS-485	2-pin
	RS-232	1 D-type male connector
Artificial Intelligence		Support for people and vehicle detection
Weights & Measures	Dimension / Weight	430 (W) x 400 (D) x 86.4 (H)mm, 4.0 KG (without HDD)
Power	Source / Consumption	+12VDC, 8.33A / 100 W Max.
Operating Temperature		-5°C ~ +60°C

※The company reserves the right on spec. modification without notice.